



NOTES

1. STREET NAME SIGNS SHALL BE FABRICATED OF VIP DIAMOND GRADE REFLECTIVE SHEETING, SINGLE FACED ON 0.125 INCH THICKNESS, 6061-T6 OR 5052-H38 ALUMINUM SIGN BLANKS (FROM STRETCHER LEVEL FLAT SHEETING) FOR MAST ARM MOUNTING.
2. ACCEPTABLE LENGTHS VARY FROM 3 FEET TO 7 FEET IN 6 INCH INCREMENTS.
3. COLORS USED FOR THE THE STREET NAME SIGNS SHALL BE WHITE (SILVER) TEXT ON GREEN BACKGROUND.
4. THE SIZES AND SPACING OF UPPER AND LOWER CASE LETTERS ARE SPECIFIED IN THE "STANDARD ALPHABETS FOR HIGHWAY SIGNS", FEDERAL HIGHWAY ADMINISTRATION, 1966 EDITION, REPRINTED APRIL, 1984.
5. SIGN FACES MAY BE FABRICATED USING EITHER EC FILM, CUT OUT LETTERS OR REVERSE SCREENED.

Charlie Keenan
TRAFFIC ENGINEER
Henry Vieregger
CITY ENGINEER

CITY OF OMAHA		PUBLIC WORKS DEPARTMENT	
STREET NAME SIGN LAYOUT TYPE " A ", MAST ARM MOUNTED 18" SIGN HEIGHT		STANDARD PLATE	6-80
		ISSUE DATE:	MARCH 26, 2003
			SHEET 1/2